

POSITIONING

ADJUSTABLE POSITIONING LANYARD

- Complete with steel carabiner with screw ring nut and one aluminium connector with double safety catch included
- Progressive length adjustment device for better work positioning

CODES AND CHARACTERISTICS

CODE	standard	L [m]	weight [g]	rope diameter [mm]	pcs
POS2	CE - EN 358	2	510	Ø11	1
POS3	CE - EN 358	3	590	Ø11	1
POS4	CE - EN 358	4	670	Ø11	1



CE

ENERGY

ADJUSTABLE ROPE WITH ENERGY ABSORBER

- Ø12 rope; one end has a knot to adjust the length, the other is sewn with an attachment knot
- Steel carabiner with screw ring nut and second steel large aperture (50 mm) carabiner with double safety catch

CODES AND CHARACTERISTICS

CODE	standard	L [m]	rope diameter [mm]	pcs
ENERGY	CE - EN 355	2	Ø12	1



CE

PLATROPE

ADJUSTABLE ROPE WITH ENERGY ABSORBER FOR PLATFORMS

- Complete with an autoblock steel carabiner and a large opening (56 mm) aluminium connector with double safety catch included
- Provided with BACK device that follows the worker both when ascending and descending, stopping any falls
- Protective case for energy absorber made of fabric with Velcro closure

CODES AND CHARACTERISTICS

CODE	standard	L [m]	weight [g]	rope diameter [mm]	pcs
PLATROPE	CE - EN 355 EN 353-2	1,9	1430	Ø11	1



CE