FALL PROTECTION AND POSITIONING

I DOUBLE SICUROPE

DOUBLE ARM ROPE WITH ENERGY ABSORBER

- Complete with steel carabiner with screw ring nut and two aluminium connectors with double safety catch
- Energy absorber with activation indicator
- Protective case for energy absorber made of fabric with Velcro closure

CODES AND CHARACTERISTICS

CODE	standard	L	weight	pcs
		[m]	[g]	
DSIC15	CE - EN 355	1,5	890	1
DSIC2	CE - EN 355	2	930	1



I SCAFFOLD DUO

DOUBLE ARM ROPE WITH ENERGY ABSORBER

- Complete with steel carabiner with screw ring nut and two aluminium large aperture (56 mm) connectors with double safety catch included
- Energy absorber with activation indicator
- Protective case for energy absorber made of fabric with Velcro closure

CODES AND CHARACTERISTICS

CODE	standard	L	weight	pcs
		[m]	[g]	
SCA15	CE - EN 355	1,5	1540	1



I SICUROPE

SINGLE ARM ROPE WITH ENERGY ABSORBER

- Complete with steel carabiners with screw ring nut
- Protective case for energy absorber made of fabric with Velcro closure
- · Energy absorber with activation indicator

CODES AND CHARACTERISTICS

CODE	standard	L	weight	pcs
		[m]	[g]	
SIC15	CE - EN 355	1,5	715	1
SIC2	CE - EN 355	2	755	1



CE



