



G-TEK® POLYKOR™ BLENDED GLOVE WITH POLYURETHANE COATED GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Polyurethane coated palm and fingertips for great abrasion resistance, excellent puncture resistance and outstanding wet/dry grip
- Knit wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing
- Washable, resistant to chemicals, water, and ultraviolet light
- Thumb / Index reinforcement for better wear resistance

APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C)



TECHNICAL DATA

MATERIAL	PolyKor™ Fiber / Polyurethane					
CONSTRUCTION	Seamless knit					
COLOR	Shell: ■ Salt & Pepper / Coating: ■ Gray					
SIZES	6 - 11					
PACKAGING	Single polybag, pack of 12, case of 72					
CASE	30cm x 32cm x 26cm					
CASE WEIGHT	6	7	8	9	10	11
	3.9 kg	4.3 Kg	4.8 Kg	4.9 Kg	5.4 Kg	5.5 Kg
COO	China					

DIMENSIONS (IN/CM)

	6	7	8	9	10	11
A	9.0 / 22.5	9.3 / 23.5	9.6 / 24.5	10 / 25.5	10.4 / 26.5	10.8 / 27.5
B	3.7 / 9.3	3.9 / 9.8	4.1 / 10.3	4.2 / 10.6	4.3 / 10.8	4.3 / 11
H	■ Purple	■ Red	■ Yellow	■ Brown	■ Black	■ Blue

PERFORMANCE PROPERTIES

EN388: 4X43C

ASTM F2992-15 ANSI Cut Level A3 (Adopted by ANSI/ISEA 02/16)

ABRASION	0	1	2	3	4	-
CUT (2003)	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (ISO 13997)	A	B	C	D	E	F

