








Conforms to EN795:2012

Bettersafe International BV, Azewijnseweg 12 SF, 4214 KC

t | + 31(0) 183 820 280

- e | info@bettersafeinternational.com
- w | www. bettersafeinternational.com

KEY SPECIFICATIONS





Ø 1200mm

Weight	300 kg
Individual Weights	24 kg
Qty Weights	12 units
Weight of posts /supports	12 kg
Width	1200 mm
Height	465 mm
Made from Recycled Materials	

MATTING SPECIFICATIONS

Elastomer	Natural
Colour	Black
Quality	Commercial
Grade	N02
Hardness	70° shore a
S.G.	1.55g/cm ³
Tensile MPA	4
Elongation	300%
Tear strength	12 kg/cm
Compression set	43%
Abrasion resistance	48/0 mm³
Operating temperature	-20° / +70° c

INSTALLATION LIMITATIONS

The Weight Angel Safety System is designed with the following limitations:

- Fall Arrest for two (2) users
- Maximum roof pitch of five (5) degrees

Roofing Materials

- Single Ply Membrane
- Single Ply Bitumen Membrane with stone covering
- Single Ply Membrane Bitumen
- Concrete Deck

Weather

- Wet surfaces are tested
- · Dry surfaces are tested