

Dynamic retractable fall arrester: 102W, 203W and 206W



Conform EN360:2002

Description: 102W and 203W Retractable fall arresters in an aluminium casing housing 25 mm wide Dyneema webbing (cut resistant) in lengths of 2.1 mtr and 3,5 mtr, which terminates with a EN 362 compliant connector which includes a swivel function. No external shock absorber.

206W Retractable fall arrester in an plastic casing housing 25 mm wide Dyneema webbing (cut resistant) in a length of 6 mtr which terminates with a EN362 compliant connector which includes a swivel function. No external shock absorber.

Material:	Webbing:	25 mm, Dyneema
	Casing:	102W and 203W aluminium. 206W plastic
	Hooks:	snaphook aluminium scaffolding hook steel scaffolding hook aluminium

Weight: 102W (without hook) 850 gram, 203W (without hook) 1150 gram and 206W (without hook) 990 gram

Length webbing: 102W = 2,1m, 203W = 3,5m and 206W = 6,0m

Article Number: **FP1-CE102WD** **102W snaphook**
 FP1-CE102WE **102W alum scaffold hook**
 FP1-CE102WF **102W steel scaffold hook**

FP2-CE203WD **203W snaphook**
 FP2-CE203WE **203W alum scaffold hook**
 FP2-CE203WF **203W steel scaffold hook**

FP2-CE206WD **206W snaphook**
 FP2-CE206WE **206W alum scaffold hook**
 FP2-CE206WF **206W steel scaffold hook**

Max load: **140 kilogram user mass**

Packaging: **Box includes a user manual**